



PAN-PIONEER Co., Ltd.

民鋒股份有限公司

SPECIFICATION

Name: 1600mm-1+4B Skip Type Single Twisting Machine

1.] Main specification:

- 1.1.) Type: Bow type, single twisting machine
- 1.2.) Application: For plastic insulated cable 5 cores twisting(round shape only)
- 1.3.) Supply core dia: 25mm Max.
- 1.4.) Revolution of rotor: 400Rpm Max.
- 1.5.) Stranding pitch: 150-1000mm Max.
- 1.6.) Pay-off bobbin: 1600mm Max. Take-up bobbin: 2600mm Max.
- 1.7.) Driven motor: HP DC motor

2.] Machine composition:

- 2.1.) 1600mm outer supply stand..... 1set
- 2.2.) 1600mm stranding cage 4sets
- 2.3.) Stranding die stand..... 1set
- 2.4.) Post forming roller unit..... 1set
- 2.5.) Length counter..... 1set
- 2.6.) 1200mm dual wheel capstan 1set
- 2.7.) 2600mm Take up stand 1set
- 2.8.) Driven motors c/w control 1set
- 2.9.) Safety cover for machine 1set



No.50 Lane 573 Ping-Dong Rd., Ping-Zhen City , Tao-Yuan County , TAIWAN , R.O.C.

Tel : +886-3-4604789 Fax : +886-3-4604788

E_mail : sales@pan-pioneer.com [Http://www.pan-pioneer.com](http://www.pan-pioneer.com)