



PAN-PIONEER Co., Ltd.
民鋒股份有限公司
SPECIFICATION

Name: Cantilever Type Pay off Stand

1.] Model:

MODEL	Drum dia (mm)	Drum width (mm)	Load (kg)	Speed (MPM)	Cable dia. (mm)
PH-100(M)	630-1000	400-800			3-15
PH-125(M)	630-1250	400-950			4-20
PH-160(M)	800-1600	500-1200			5-30
PH-180(M)	1000-1800	500-1200			5-40
PH-200(M)	1250-2000	950-1600			6-50

Remarks: (M): with motor driving utility.

2.] Features:

- 2.1.) Type: Shaftless type, drum loaded by cantilever arms with hydraulic lifters both side. Drum lock/release done by motors
- 2.2.) An optional cable-sending device is available
- 2.3.) Application: for cable pay off in the process of cable manufacturing or rewinding

3.] Machine composition:

- 3.1.) Pay off stand 1set
- 3.2.) Hydraulic unit..... 1set
- 3.3.) Motorize cable sending... 1set (Option)

4.] Detail specifications:

- 4.1.) Drum lock/release:
 - 4.1.1.) Shaft less type, drum lock or release are done by two cantilever arms each side. Open and close of arms done by a pair of screws and driven by 400W motor with reduction motor each side. (Model PH-11 1000mm pay off stand is done by handle screws)
 - 4.1.2.) Operation: For up/down and open/close of drum, just operate a 4-way directions switch on each side of the arms.
 - 4.1.3.) A select switch is provided for Independent and/or synchronous operation on each side of arms.



PAN-PIONEER Co., Ltd.
民鋒股份有限公司
SPECIFICATION

